



# VANDAL



## AA-EB-2G-CL

### Vandal Resistant Double Gang Outlet Security Box with Keyed Cylinder Lock



#### Features:

- Vandal Resistant Design
- Made in USA
- 10 Year Vandalism Warranty on 12g
- Hidden Keyed Cylinder Lock
- Spray & Drip Deflective
- Surface Mounted
- Corrosion Resistant
- Flexible Applications
- Removable Backplate
- LEED Sustainable Materials
- Bottom & Rear Conduit Access
- Fits Most Double-Gang Duplex Receptacle Boxes (Not Included)
- Removable Backing Plate for Surface & Recessed Applications
- Accommodates 1/2" & 3/4" Conduit on Bottom and Back

#### Dimensions:

- Exterior: 5 5/8" x 7 3/4" x 4 3/4" (WxHxD)
- Interior: 5" x 7" x 4 3/8" (WxHxD)
- Rear opening size: 5" x 4 3/4" (WxH)

**Weight:** 8 lbs

#### Material Options:

- 12-gauge 304L Stainless Steel
- 12-gauge 316L Stainless Steel

#### Model Names:

- AA-EB-2G-CL-304L-12g
- AA-EB-2G-CL-316L-12g

**Finish:** Stainless Steel Satin # 4 Finish

**Compatibility:** Fits most single-gang duplex receptacle boxes (not included). 1/2" and 3/4" conduit, with up to 0.922" outside diameter. Designed Specifically for

- [Greenfield B232BRS Box](#)
- [Greenfield C2GFI2PS Weatherproof Cover](#)

**Mounting:** 3/8" Surface Mounting Hole Placements. Mounting Hardware is not included due to wide variety of mounting surfaces. Installer must select 3/8" hardware suitable for application.

**Installation:** Secure fixture to wall with appropriate 3/8" stainless steel anchoring hardware (not provided) for optimal installation strength. Recommended 3/4" or greater back bracing for walls. Partitions may require T-nuts or other suitable anchoring devices. When possible it is recommended that units be through bolted back to back providing optimal installation strength.

**Guide Specification:** Security Box shall be constructed with 12 gauge 304L or 12 gauge 316L Stainless Steel joined w/ TIG welds and edges deburred. Security Box shall not be cross-metal contaminated during manufacturing construction. Security Box shall provide protective cover against drip and spray. Security Box shall have 3/8" mounting holes. Security Box shall accommodate standard double-gang duplex receptacle box styles. 316L SS shall be used for US Navy maritime use or if exposure to salt water is prevalent.

