



AA-EB-2170

Vandal Resistant Locking Surface Mount Dryer Outlet Enclosure



Features:

- Vandal Resistant Design
- Made in USA
- Low Profile for Recessed Outlet Applications
- Keyed Cylinder Lock
- Surface Mounted
- Corrosion Resistant
- Flexible Applications
- LEED Sustainable Materials

Dimensions:

- Exterior: $7 \frac{7}{8}$ " x $8 \frac{3}{4}$ " x 1" (WxHxD)
- Interior: $7 \frac{3}{8}$ " x $8 \frac{3}{8}$ " x $\frac{3}{4}$ " (WxHxD)
- Rear opening size: $5 \frac{7}{8}$ " x $5 \frac{7}{8}$ " (WxH)

Weight: 4.5 lbs

Material Options:

- 12-gauge 304L Stainless Steel
- 12-gauge 316L Stainless Steel
- 16-gauge 304L Stainless Steel

Model Names:

- AA-EB-2170-304L-12g
- AA-EB-2170-316L-12g
- AA-EB-2170-304L-16g

Finish: Stainless Steel Satin # 4 Finish

Mounting: $\frac{3}{8}$ " Surface Mounting Hole Placements. Mounting Hardware is not included due to wide variety of mounting surfaces. Installer must select $\frac{3}{8}$ " hardware suitable for application.

Installation: Secure fixture to wall with appropriate $\frac{3}{8}$ " stainless steel anchoring hardware (not provided) for optimal installation strength. Recommended $\frac{3}{4}$ " or greater back bracing for walls. Partitions may require T-nuts or other suitable anchoring devices. When possible it is recommended that units be through-bolted back to back providing optimal installation strength.

Guide Specification: Box shall be constructed with 12- or 16-gauge 304L or 12 gauge 316L Stainless Steel joined with TIG welds and edges deburred. Box shall not be cross-metal contaminated during manufacturing construction. Box shall provide protective cover against drip and spray. Box shall have $\frac{3}{8}$ " mounting holes. 316L SS shall be used for US Navy maritime use or if exposure to salt water is prevalent.

